



ITEM	PART NO.	QTY.	DESCRIPTION
------	----------	------	-------------

NOTES:

- 3 WIRE ENDS OF ITEMS 11,12,13, & 15 TO BE STRIPED 0.200 INCH AND TINNED, BEFORE SOLDERING.
- 4 ITEMS 12 AND 13 TO BE CUT INTO TWO 19.00 INCH HARNESSES EACH. TRIM FOILED SHIELD BACK AS LITTLE AS POSSIBLE. ALL DATA PAIRS EXITING FOILED SHIELD TO BE TWISTED TO TERMINATION POINT. MEASURE LENGTH OF INDIVIDUAL WIRES ACCORDING TO IT'S SPECIFIC LOCATION. ADD 2.50 OF SHRINK TUBING TO ALL FOILED TWISTED PAIRS EXITING CABLE AND THEN ADD LARGER SHRINK TUBING OVER REMAINING WIRES. ADD 2.50 OF SHRINK TUBING TO EACH INDIVIDUALLY FOILED WIRE EXITING CABLE AND ADD LARGER SHRINK TUBING OVER REMAINING WIRES.
- 5 USE SHRINK TUBING ON EACH WIRE AND SHRINK THE TUBING BEFORE STRIPPING. (THIS WILL HELP PROTECT WIRE INSULATION.)

C		ADDED THIS SHEET		6/20/00	G.S.			
A		ADDED ARCNET CHANGES		3-9-00	G.S.			
		ORIGINAL ISSUE						
REVISION LETTER	CLASS REVIEW	REVISIONS			DATE	CHANGED BY	CHECKED BY	APPROVED BY
<div>LOS ALAMOS</div> <div>LOS ALAMOS NATIONAL LABORATORY</div> <div>LOS ALAMOS, NEW MEXICO 87545</div>					CLASSIFICATION OF DRAWING: UNCL			
					PART: UNCL		TITLE BLOCK: UNCL	
					TITLE			
					CBP-1			
					CATHODE BKPLANE			
					ASSEMBLY			
	SIGNATURE	DATE	GROUP					
ORIGINATED	M.ECHAVE	5/14/99	NIS-4					
DRAWN	G.SAEWERT	6/20/00	NIS-4					
CHECKED								
PROJ. ENGR.								
APPROVED								
RELEASED								
				SCALE	TOTAL SHEETS	DRAWING NO.		SHEET SIZE
				NONE	3	10Y-226430		D8